

Materialprüfungsamt Nordrhein-Westfalen

Prüfen • Überwachen • Zertifizieren

**Certificate of conformity of the factory production control
0432-CPR-00133-31 (EN)**

Version 01

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction products Regulation or CPR), this certificate applies to the construction product

flexible, double wall flue liners

made of stainless steel: 1.4404; 1.4571; 1.4301

"KFP PROFIFLEX"

(for a detailed product description see annex 1 of this certificate)

placed on the market under the name or trade mark of

Kominus Polska Sp. z o.o.Łęzkowice 112
32-015 Klaj / Poland

and produced in the manufacturing plant(s)

Kominus Polska Sp. z o.o.Łęzkowice 112
32-015 Klaj / Poland

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s)

EN 1856-2:2009under **system 2+** are applied and that**the factory production control is assessed to be in conformity
with the applicable requirements**

This certificate was first issued on 01.01.2015 and will remain valid until 09.12.2024 as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

Dortmund, 10.12.2019

on behalf

Dipl.-Ing. Hönig
Head of Certification Body (Dept. 21)

This Certificate consists of 1 page and 1 annex(es).

This Certificate replaces the Certificate no.
0432-CPR-900133-611/-612 dated 01.01.2015, Version 1.0.The original of this document was issued in German language.
In case of doubt only the German version is valid.

Vom Hersteller erklärte Eigenschaften für / Declared conditions by the manufacturer for:

	Art der Abgasanlage / Leitung <i>type of chimney / flue pipe</i>	Harmonisierte Norm <i>standard</i>	Produktbeschreibung <i>Product description</i>
01	"KFP-PROFIFLEX" Flexible Innenrohre <i>Flexible flue liners</i> Rohr / <i>pipe</i> : 1.4404 / 1.4571 Wanddicke / <i>wall thickness</i> : $\geq 0,10 + 0,10$ mm(-10 %)	EN 1856-2:2009	T450 – P1 – D – Vm – L50020 – G T450 – P1 – W – Vm – L50020 – O DN 80 - 300
02	"KFP-PROFIFLEX" Flexible Innenrohre / <i>Flexible flue liners</i> Rohr / <i>pipe</i> : 1.4301 Wanddicke / <i>wall thickness</i> : $\geq 0,10 + 0,10$ mm(-10 %)	EN 1856-2:2009	T450 – P1 – D – Vm – L20020 – G T450 – P1 – W – Vm – L20020 – O DN 80 - 300

2. Ausfertigung / *second copy*